



## Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Code: M400000F  
Product name: BCR EPOXY 21 COMP A  
Chemical name and synonym: Mastic based pure epoxy resin  
UFI: WH00-Y0JQ-400Y-M0HF

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Bi-component injection system for chemical anchor on construction materials.

#### 1.3. Details of the supplier of the safety data sheet

Name: Bossong SpA  
Full address: via E. Fermi, 51  
District and Country: 24050 Grassobbio (BG)  
Italia  
Tel. 035-3846011  
Fax 035-3846012

e-mail address of the competent person responsible for the Safety Data Sheet: tek@bossong.com

#### 1.4. Emergency telephone number

For urgent inquiries refer to: Ospedale NIGUARDA Milano tel. +39 0266101029  
<http://www.centroantiveleni.org/>

Centro Antiveleni di Bergamo (CAV Ospedali Riuniti) tel: 800 883300  
Centro Antiveleni di Roma (CAV Policlinico Gemelli) tel: +39 06 3054343

### SECTION 2. Hazards identification

#### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

#### Hazard classification and indication:

Germ cell mutagenicity, category 2	H341	Suspected of causing genetic defects.
Reproductive toxicity, category 1B	H360F	May damage fertility.
Skin corrosion, category 1C	H314	Causes severe skin burns and eye damage.
Serious eye damage, category 1	H318	Causes serious eye damage.
Skin sensitization, category 1	H317	May cause an allergic skin reaction.
Hazardous to the aquatic environment, chronic toxicity,	H411	Toxic to aquatic life with long lasting effects.


**M400000F - BCR EPOXY 21 COMP A**

category 2

**2.2. Label elements**

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:

Danger

Hazard statements:

<b>H341</b>	Suspected of causing genetic defects.
<b>H360F</b>	May damage fertility.
<b>H314</b>	Causes severe skin burns and eye damage.
<b>H317</b>	May cause an allergic skin reaction.
<b>H411</b>	Toxic to aquatic life with long lasting effects.
<b>EUH205</b>	Contains epoxy constituents. May produce an allergic reaction. Restricted to professional users.

Precautionary statements:

<b>P260</b>	Do not breathe dust / fume / gas / mist / vapours / spray.
<b>P201</b>	Obtain special instructions before use.
<b>P305+P351+P338</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
<b>P303+P361+P353</b>	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
<b>P280</b>	Wear protective gloves/ protective clothing / eye protection / face protection.
<b>P310</b>	Immediately call a POISON CENTER / doctor / . . .
<b>P501</b>	Dispose of contents/container in accordance with national regulations.

<b>Contains:</b>	1,3-propanediol, 2-ethyl-2-(hydroxymethyl)-, polymer with 2-(chloromethyl)oxirane / trimethylolpropane triglycidylether PRODOTTO DI REAZIONE: BISFENOLO-A-EPICLORIDRINA BISFENOLO F
------------------	---

**2.3. Other hazards**On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.The product does not contain substances with endocrine disrupting properties in concentration  $\geq$  0.1%.**SECTION 3. Composition/information on ingredients**

**M400000F - BCR EPOXY 21 COMP A****3.2. Mixtures**

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
<b>BISFENOLO F</b>		
CAS 9003-36-5	$17 \leq x < 25$	Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Chronic 2 H411
EC 500-006-8		
INDEX -		
REACH Reg. 01-2119454392-40		
<b>PRODOTTO DI REAZIONE: BISFENOLO-A-EPICLORIDRINA</b>		
CAS 1675-54-3	$17 \leq x < 25$	Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Chronic 2 H411
EC 216-823-5		Skin Irrit. 2 H315: $\geq 5\%$ , Eye Irrit. 2 H319: $\geq 5\%$
INDEX -		
REACH Reg. 01-2119456619-26		
<b>1,3-propanediol, 2-ethyl-2-(hydroxymethyl)-, polymer with 2-(chloromethyl)oxirane / trimethylolpropane triglycidylether</b>		
CAS 30499-70-8	$9 \leq x < 17$	Muta. 2 H341, Repr. 1B H360F, Skin Corr. 1C H314, Eye Dam. 1 H318, Skin Sens. 1 H317, Aquatic Chronic 2 H411
EC 608-489-8		
INDEX -		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

Quartz (SiO<sub>2</sub>) - CAS 14808-60-7 - C%:  $\geq 50$  -  $< 80$ :

The quartz contained in the product is classified as non-hazardous. Furthermore, being linked to the other liquid / pasty components of the mixture, it is not freely available during use. The final product has a pasty consistency and the limits of exposure to inhalable dusts are not relevant.

**SECTION 4. First aid measures****4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

**4.2. Most important symptoms and effects, both acute and delayed**

Specific information on symptoms and effects caused by the product are unknown.

**4.3. Indication of any immediate medical attention and special treatment needed**

Information not available

**SECTION 5. Firefighting measures**

**M400000F - BCR EPOXY 21 COMP A****5.1. Extinguishing media**

## SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

## UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

**5.2. Special hazards arising from the substance or mixture**

## HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

**5.3. Advice for firefighters**

## GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

## SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

**SECTION 6. Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

**6.2. Environmental precautions**

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

**6.3. Methods and material for containment and cleaning up**

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

**6.4. Reference to other sections**

Any information on personal protection and disposal is given in sections 8 and 13.

**SECTION 7. Handling and storage****7.1. Precautions for safe handling**

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

**M400000F - BCR EPOXY 21 COMP A****7.2. Conditions for safe storage, including any incompatibilities**

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

Store in a well ventilated place, storage range temperature between 5°C and 30°C. Keeping the containers closed when not used. Do not smoke while handling. Keep far away from sources of heat, naked flames and sparks and other sources of ignition. Make sure that equipment is available for cooling the vessels, to prevent the danger of overpressure and overheating in the event of fire in the vicinity.

**7.3. Specific end use(s)**

Information not available

**SECTION 8. Exposure controls/personal protection****8.1. Control parameters**

Quartz (SiO<sub>2</sub>):

The quartz contained in the product is classified as non-hazardous. Furthermore, being linked to the other liquid / pasty components of the mixture, it is not freely available during use. The final product has a pasty consistency and the limits of exposure to inhalable dusts are not relevant.

**8.2. Exposure controls**

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

**HAND PROTECTION**

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

**SKIN PROTECTION**

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

**EYE PROTECTION**

Wear airtight protective goggles (see standard EN 166).

**RESPIRATORY PROTECTION**

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

**ENVIRONMENTAL EXPOSURE CONTROLS**

**M400000F - BCR EPOXY 21 COMP A**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

**SECTION 9. Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Properties	Value	Information
Appearance	Solid Pasty	
Colour	white	
Odour	characteristic	
Melting point / freezing point	Not available	
Initial boiling point	Not available	
Flammability	Not available	
Lower explosive limit	Not available	
Upper explosive limit	Not available	
Flash point	Not available	
Auto-ignition temperature	Not available	
pH	Not available	
Kinematic viscosity	Not available	
Solubility	insoluble in water	Reason for missing data:substance/mixture is non-soluble (in water)
Partition coefficient: n-octanol/water	Not available	
Vapour pressure	Not available	
Density and/or relative density	1.40 - 1.60 kg/l	
Relative vapour density	Not available	
Particle characteristics	Not applicable	

**9.2. Other information**

## 9.2.1. Information with regard to physical hazard classes

Information not available

## 9.2.2. Other safety characteristics

Information not available

**SECTION 10. Stability and reactivity****10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.



**M400000F - BCR EPOXY 21 COMP A**

**10.2. Chemical stability**

The product is stable in normal conditions of use and storage.

To avoid the exposure on the sunlight.

**10.3. Possibility of hazardous reactions**

No hazardous reactions are foreseeable in normal conditions of use and storage.

**10.4. Conditions to avoid**

None in particular. However the usual precautions used for chemical products should be respected.

**10.5. Incompatible materials**

Information not available

**10.6. Hazardous decomposition products**

Information not available

**SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available



**M400000F - BCR EPOXY 21 COMP A**

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture:	Not classified (no significant component)
ATE (Oral) of the mixture:	Not classified (no significant component)
ATE (Dermal) of the mixture:	Not classified (no significant component)

PRODOTTO DI REAZIONE: BISFENOLO-A-EPICLORIDRINA

LD50 (Dermal):	23000 mg/kg ratto
LD50 (Oral):	15000 mg/kg ratto

BISFENOLO F

LD50 (Oral):	5000 mg/kg RATTO
--------------	------------------

SKIN CORROSION / IRRITATION

Corrosive for the skin

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

Respiratory sensitization

Information not available

Skin sensitization





**M400000F - BCR EPOXY 21 COMP A**

Information not available

GERM CELL MUTAGENICITY

Suspected of causing genetic defects

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

May damage fertility

Adverse effects on sexual function and fertility

Information not available

Adverse effects on development of the offspring

Information not available

Effects on or via lactation

Information not available

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

Target organs

Information not available



Route of exposure

Information not available

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

Target organs

Information not available

Route of exposure

Information not available

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

**11.2. Information on other hazards**

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

## SECTION 12. Ecological information

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it have negative effects on aquatic environment.

**12.1. Toxicity**

PRODOTTO DI REAZIONE: BISFENOLO-A-  
EPICLORIDRINA

LC50 - for Fish 12 mg/l/96h

EC50 - for Algae / Aquatic Plants 94 mg/l/72h

**12.2. Persistence and degradability**

**M400000F - BCR EPOXY 21 COMP A**

PRODOTTO DI REAZIONE: BISFENOLO-A-  
EPICLORIDRINA

Solubility in water 0,1 - 100 mg/l

NOT rapidly degradable

**12.3. Bioaccumulative potential**

PRODOTTO DI REAZIONE: BISFENOLO-A-  
EPICLORIDRINA

Partition coefficient: n-octanol/water > 2,918

BCF 31

**12.4. Mobility in soil**

PRODOTTO DI REAZIONE: BISFENOLO-A-  
EPICLORIDRINA

Partition coefficient: soil/water 2,65

**12.5. Results of PBT and vPvB assessment**

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

**12.6. Endocrine disrupting properties**

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

**12.7. Other adverse effects**

Information not available

**SECTION 13. Disposal considerations**

Non-hardened material (such as expired or damaged products and/or rejects): e.g.

08 04 09\* Glue and sealing materials waste containing organic solvents or other dangerous substances

Hardened material, e.g.:

08 04 10 Glue and sealing materials waste or other dangerous substances, other than classified under 08 04 09.

Contaminated packaging

Uncontaminated packaging may be taken for recycling.

Packaging that cannot be cleaned should be disposed of as for product.

15 01 10\* Packaging containing residues of or contaminated by dangerous substances

**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.



**M400000F - BCR EPOXY 21 COMP A**

**CONTAMINATED PACKAGING**

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

**SECTION 14. Transport information**

**14.1. UN number or ID number**

ADR / RID, IMDG, IATA: 1759

**Not restricted goods for transport regulation. Net quantity per pack less than 5 litres. ADR Special Provision SP375, IATA-DGR Special provision A197 and IMDG-Code 2.10.2.7**

**14.2. UN proper shipping name**

ADR / RID: CORROSIVE SOLID, N.O.S. MIXTURE  
IMDG: CORROSIVE SOLID, N.O.S. MIXTURE  
IATA: CORROSIVE SOLID, N.O.S. MIXTURE

**14.3. Transport hazard class(es)**

ADR / RID: Class: 8 Label: 8  
IMDG: Class: 8 Label: 8  
IATA: Class: 8 Label: 8



**14.4. Packing group**

ADR / RID, IMDG, IATA: III

**14.5. Environmental hazards**

**Dangerous for environment.**

**ADR 5.2.1.8.1 derogation applies (quantity of liquids ≤ 5 litres or net mass of solids ≤ 5 kg).  
ADR Special Provision SP375, IATA-DGR Special provision A197 and IMDG-Code 2.10.2.7**

ADR / RID: Environmentally Hazardous  
IMDG: Marine Pollutant  
IATA: NO



For Air transport, environmentally hazardous mark is only mandatory for UN 3077 and UN 3082.

**14.6. Special precautions for user**



**M400000F - BCR EPOXY 21 COMP A**

ADR / RID:	HIN - Kemler: 80	Limited Quantities: 5 kg	Tunnel restriction code: (E)
	Special provision: 274		
IMDG:	EMS: F-A, S-B	Limited Quantities: 5 kg	
IATA:	Cargo:	Maximum quantity: 100 Kg	Packaging instructions: 864
	Pass.:	Maximum quantity: 25 Kg	Packaging instructions: 860
	Special provision:	A3, A803	

**14.7. Maritime transport in bulk according to IMO instruments**

Information not relevant

**SECTION 15. Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EU: E2

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

None

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

Not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage  $\geq$  than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

**M400000F - BCR EPOXY 21 COMP A**Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

**15.2. Chemical safety assessment**

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

**SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Muta. 2</b>	Germ cell mutagenicity, category 2
<b>Repr. 1B</b>	Reproductive toxicity, category 1B
<b>Skin Corr. 1C</b>	Skin corrosion, category 1C
<b>Eye Dam. 1</b>	Serious eye damage, category 1
<b>Eye Irrit. 2</b>	Eye irritation, category 2
<b>Skin Sens. 1</b>	Skin sensitization, category 1
<b>Aquatic Chronic 2</b>	Hazardous to the aquatic environment, chronic toxicity, category 2
<b>H341</b>	Suspected of causing genetic defects.
<b>H360F</b>	May damage fertility.
<b>H314</b>	Causes severe skin burns and eye damage.
<b>H318</b>	Causes serious eye damage.
<b>H319</b>	Causes serious eye irritation.
<b>H317</b>	May cause an allergic skin reaction.
<b>H411</b>	Toxic to aquatic life with long lasting effects.
<b>EUH205</b>	Contains epoxy constituents. May produce an allergic reaction.

**LEGEND:**

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration

**M400000F - BCR EPOXY 21 COMP A**

- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

**GENERAL BIBLIOGRAPHY**

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
  2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
  3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
  4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
  5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
  6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
  7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
  8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
  9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
  10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
  11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
  12. Regulation (EU) 2016/1179 (IX Atp. CLP)
  13. Regulation (EU) 2017/776 (X Atp. CLP)
  14. Regulation (EU) 2018/669 (XI Atp. CLP)
  15. Regulation (EU) 2019/521 (XII Atp. CLP)
  16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
  17. Regulation (EU) 2019/1148
  18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
  19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
  20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
  21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- The Merck Index. - 10th Edition
  - Handling Chemical Safety
  - INRS - Fiche Toxicologique (toxicological sheet)
  - Patty - Industrial Hygiene and Toxicology
  - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
  - IFA GESTIS website
  - ECHA website
  - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

**Note for users:**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

**CALCULATION METHODS FOR CLASSIFICATION**

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

**Changes to previous review:**

The following sections were modified:

11 / 12 / 13 / 14.



## Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Code: M400002F  
Product name: BCR EPOXY 21 COMP B  
Chemical name and synonym: Mastic based hardener for pure epoxy system  
UFI: UM00-G083-F00F-9C3H

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Bi-component injection system for chemical anchor on construction materials.

#### 1.3. Details of the supplier of the safety data sheet

Name: Bossong SpA  
Full address: via E. Fermi, 51  
District and Country: 24050 Grassobbio (BG)  
Italia  
Tel. 035-3846011  
Fax 035-3846012

e-mail address of the competent person responsible for the Safety Data Sheet: tek@bossong.com

#### 1.4. Emergency telephone number

For urgent inquiries refer to: Ospedale NIGUARDA Milano tel. +39 0266101029  
<http://www.centroantiveleni.org/>

Centro Antiveleni di Bergamo (CAV Ospedali Riuniti) tel: 800 883300  
Centro Antiveleni di Roma (CAV Policlinico Gemelli) tel: +39 06 3054343

### SECTION 2. Hazards identification

#### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

#### Hazard classification and indication:

Reproductive toxicity, category 1B	H360F	May damage fertility.
Acute toxicity, category 4	H302	Harmful if swallowed.
Skin corrosion, category 1	H314	Causes severe skin burns and eye damage.
Serious eye damage, category 1	H318	Causes serious eye damage.
Skin sensitization, category 1	H317	May cause an allergic skin reaction.
Hazardous to the aquatic environment, chronic toxicity,	H412	Harmful to aquatic life with long lasting effects.



**M400002F - BCR EPOXY 21 COMP B**

category 3

**2.2. Label elements**

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:

Danger

Hazard statements:

<b>H360F</b>	May damage fertility.
<b>H302</b>	Harmful if swallowed.
<b>H314</b>	Causes severe skin burns and eye damage.
<b>H317</b>	May cause an allergic skin reaction.
<b>H412</b>	Harmful to aquatic life with long lasting effects.
<b>EUH071</b>	Corrosive to the respiratory tract. Restricted to professional users.

Precautionary statements:

<b>P260</b>	Do not breathe dust / fume / gas / mist / vapours / spray.
<b>P201</b>	Obtain special instructions before use.
<b>P305+P351+P338</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
<b>P303+P361+P353</b>	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
<b>P280</b>	Wear protective gloves/ protective clothing / eye protection / face protection.
<b>P310</b>	Immediately call a POISON CENTER / doctor / . . .
<b>P501</b>	Dispose of contents/container in accordance with national regulations.

**Contains:**

4,4'-ISOPROPYLIDENEDIPHENOL  
M-PHENYLENEBIS (METHYLAMINE)  
Prodotti di reazione oligomerici della formaldeide con 4,4'-isopropilidendifenolo e m-fenilenbis(metilammina)  
2,4,6-TRIS(DIMETHYLAMINOMETHYL) PHENOL

**2.3. Other hazards**On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.The product contains substances with endocrine disrupting properties in concentration  $\geq$  0.1%.

4,4'-ISOPROPYLIDENEDIPHENOL

**M400002F - BCR EPOXY 21 COMP B****SECTION 3. Composition/information on ingredients****3.2. Mixtures**

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
<b>M-PHENYLENEBIS (METHYLAMINE)</b> CAS 1477-55-0 EC 216-032-5 INDEX - REACH Reg. 01-2119480150-50	17 ≤ x < 25	Acute Tox. 4 H302, Acute Tox. 4 H332, Skin Corr. 1B H314, Eye Dam. 1 H318, Skin Sens. 1B H317, Aquatic Chronic 3 H412, EUH071 STA Oral: 500 mg/kg, STA Inhalation vapours: 11 mg/l
<b>BENZYL ALCOHOL</b> CAS 100-51-6 EC 202-859-9 INDEX 603-057-00-5 REACH Reg. 01-2119492630-38	10 ≤ x < 17	Acute Tox. 4 H302, Acute Tox. 4 H332, Eye Irrit. 2 H319 LD50 Oral: 1230 mg/kg, STA Inhalation vapours: 11 mg/l
<b>Prodotti di reazione oligomerici della formaldeide con 4,4'- isopropilidendifenolo e m- fenilenbis(metilammina)</b> CAS 161278-17-7 EC 500-607-5 INDEX -	5 ≤ x < 9	Acute Tox. 4 H302, Acute Tox. 4 H312, Skin Corr. 1 H314, Eye Dam. 1 H318, Skin Sens. 1 H317, Aquatic Chronic 4 H413 STA Oral: 500 mg/kg, STA Dermal: 1100 mg/kg
<b>2,4,6- TRIS(DIMETHYLAMINOMETHYL) PHENOL</b> CAS 90-72-2 EC 202-013-9 INDEX 603-069-00-0 REACH Reg. 01-2119560597-27	5 ≤ x < 9	Acute Tox. 4 H302, Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin Sens. 1B H317 STA Oral: 500 mg/kg
<b>4,4'-ISOPROPYLIDENEDIPHENOL</b> CAS 80-05-7 EC 201-245-8 INDEX 604-030-00-0 REACH Reg. 01-2119457856-23	3 ≤ x < 5	Repr. 1B H360F, Eye Dam. 1 H318, STOT SE 3 H335, Skin Sens. 1 H317, Aquatic Chronic 2 H411
<b>3-(diethylammino)propan-1,2-diolo</b> CAS 621-56-7 EC 210-693-3 INDEX -	1 ≤ x < 5	Desen. Expl. 3 H207, Eye Irrit. 2 H319, Skin Irrit. 2 H315

The full wording of hazard (H) phrases is given in section 16 of the sheet.

Quartz (SiO<sub>2</sub>) - CAS 14808-60-7 - C%: ≥50 - <80:

The quartz contained in the product is classified as non-hazardous. Furthermore, being linked to the other liquid / pasty components of the mixture, it is not freely available during use. The final product has a pasty consistency and the limits of exposure to inhalable dusts are not relevant.

**M400002F - BCR EPOXY 21 COMP B****SECTION 4. First aid measures****4.1. Description of first aid measures**

**EYES:** Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

**SKIN:** Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

**INGESTION:** Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

**INHALATION:** Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

**4.2. Most important symptoms and effects, both acute and delayed**

Specific information on symptoms and effects caused by the product are unknown.

**4.3. Indication of any immediate medical attention and special treatment needed**

Information not available

**SECTION 5. Firefighting measures****5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

**UNSUITABLE EXTINGUISHING EQUIPMENT**

None in particular.

**5.2. Special hazards arising from the substance or mixture****HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Do not breathe combustion products.

**5.3. Advice for firefighters****GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

**SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS**

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

**SECTION 6. Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

**6.2. Environmental precautions**

**M400002F - BCR EPOXY 21 COMP B**

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

**6.3. Methods and material for containment and cleaning up**

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

**6.4. Reference to other sections**

Any information on personal protection and disposal is given in sections 8 and 13.

**SECTION 7. Handling and storage****7.1. Precautions for safe handling**

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

**7.2. Conditions for safe storage, including any incompatibilities**

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

Store in a well ventilated place, storage range temperature between 5°C and 30°C. Keeping the containers closed when not used. Do not smoke while handling. Keep far away from sources of heat, naked flames and sparks and other sources of ignition. Make sure that equipment is available for cooling the vessels, to prevent the danger of overpressure and overheating in the event of fire in the vicinity.

**7.3. Specific end use(s)**

Information not available

**SECTION 8. Exposure controls/personal protection****8.1. Control parameters**

Regulatory References:

CZE	Česká Republika	Nařízení vlády č. 41/2020 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2021

**M-PHENYLENEBIS (METHYLAMINE)**

**M400002F - BCR EPOXY 21 COMP B****Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	
VLEP	FRA			0,1		
TLV-ACGIH				0,018 (C)		SKIN

**BENZYL ALCOHOL****Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	
TLV	CZE	40	8,88	80	17,76	
AGW	DEU	22	5	44	10	SKIN 11

**4,4'-ISOPROPYLIDENEDIPHENOL****Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	
TLV	CZE	2		5		INHAL
AGW	DEU	5		5 (C)		INHAL
VLEP	FRA	2				
VLEP	ITA	2				INHAL
VLEP	ITA	2				SKIN
WEL	GBR	2				
OEL	EU	2				INHAL

## Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

Quartz (SiO<sub>2</sub>):

The quartz contained in the product is classified as non-hazardous. Furthermore, being linked to the other liquid / pasty components of the mixture, it is not freely available during use. The final product has a pasty consistency and the limits of exposure to inhalable dusts are not relevant.

**8.2. Exposure controls**

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

**HAND PROTECTION**

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

**M400002F - BCR EPOXY 21 COMP B****SKIN PROTECTION**

Wear category III professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

**EYE PROTECTION**

Wear a hood visor or protective visor combined with airtight goggles (see standard EN 166).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

**RESPIRATORY PROTECTION**

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

**ENVIRONMENTAL EXPOSURE CONTROLS**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

**SECTION 9. Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Properties	Value	Information
Appearance	Solid Pasty	
Colour	black	
Odour	amino	
Melting point / freezing point	Not available	
Initial boiling point	Not available	
Flammability	Not available	
Lower explosive limit	Not available	
Upper explosive limit	Not available	
Flash point	Not available	
Auto-ignition temperature	Not available	
pH	Not available	
Kinematic viscosity	Not available	
Solubility	immiscible with water	Reason for missing data:substance/mixture is non-soluble (in water)
Partition coefficient: n-octanol/water	Not available	
Vapour pressure	Not available	
Density and/or relative density	1,40 - 1,60 kg/l	
Relative vapour density	Not available	



**M400002F - BCR EPOXY 21 COMP B**

Particle characteristics Not applicable

**9.2. Other information**

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Information not available

**SECTION 10. Stability and reactivity**

**10.1. Reactivity**

The product can decompose and/or react violently.

BENZYL ALCOHOL

Decomposes at temperatures above 870°C/1598°F.Possibility of explosion.

**10.2. Chemical stability**

See previous paragraph.

To avoid the exposure on the sunlight.

**10.3. Possibility of hazardous reactions**

See paragraph 10.1.

BENZYL ALCOHOL

May react dangerously with: hydrobromic acid,iron,oxidising agents,sulphuric acid.Risk of explosion on contact with: phosphorus trichloride.

**10.4. Conditions to avoid**

As the product decomposes even at ambient temperature, it must be stored and used at a controlled temperature. Avoid violent blows.

BENZYL ALCOHOL

Avoid exposure to: air,sources of heat,naked flames.

**10.5. Incompatible materials**

BENZYL ALCOHOL

Incompatible with: sulphuric acid,oxidising substances,aluminium.



**M400002F - BCR EPOXY 21 COMP B**

**10.6. Hazardous decomposition products**

Information not available

**SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

Corrosive to the respiratory tract.

ATE (Inhalation - vapours) of the mixture:	> 20 mg/l
ATE (Oral) of the mixture:	1001,79 mg/kg
ATE (Dermal) of the mixture:	>2000 mg/kg

M-PHENYLENEBIS (METHYLAMINE)



**M400002F - BCR EPOXY 21 COMP B**

LD50 (Dermal): 3100 mg/kg Rat  
LD50 (Oral): > 200 mg/kg Rat - Sprague-Dawley  
STA (Oral): 500 mg/kg estimate from table 3.1.2 of Annex I of the CLP  
(figure used for calculation of the acute toxicity estimate of the mixture)

LC50 (Inhalation vapours): 1,34 mg/l Rat - Wistar  
STA (Inhalation vapours): 11 mg/l estimate from table 3.1.2 of Annex I of the CLP  
(figure used for calculation of the acute toxicity estimate of the mixture)

**BENZYL ALCOHOL**

LD50 (Dermal): 2000 mg/kg Rabbit  
LD50 (Oral): 1230 mg/kg Rat  
LC50 (Inhalation vapours): > 4,1 mg/l/4h Rat  
STA (Inhalation vapours): 11 mg/l estimate from table 3.1.2 of Annex I of the CLP  
(figure used for calculation of the acute toxicity estimate of the mixture)

**2,4,6-TRIS(DIMETHYLAMINOMETHYL) PHENOL**

STA (Oral): 500 mg/kg estimate from table 3.1.2 of Annex I of the CLP  
(figure used for calculation of the acute toxicity estimate of the mixture)

**Prodotti di reazione oligomerici della formaldeide con 4,4'-isopropilidendifenolo e m-fenilenbis(metilammina)**

STA (Oral): 500 mg/kg estimate from table 3.1.2 of Annex I of the CLP  
(figure used for calculation of the acute toxicity estimate of the mixture)

STA (Dermal): 1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP  
(figure used for calculation of the acute toxicity estimate of the mixture)

**4,4'-ISOPROPYLIDENEDIPHENOL**

LD50 (Dermal): 3000 mg/kg Rabbit  
LD50 (Oral): 5000 mg/kg

**SKIN CORROSION / IRRITATION**

Corrosive for the skin

**SERIOUS EYE DAMAGE / IRRITATION**

Causes serious eye damage

**RESPIRATORY OR SKIN SENSITISATION**

Sensitising for the skin



**M400002F - BCR EPOXY 21 COMP B**

Respiratory sensitization

Information not available

Skin sensitization

Information not available

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

May damage fertility

Adverse effects on sexual function and fertility

Information not available

Adverse effects on development of the offspring

Information not available

Effects on or via lactation

Information not available



**M400002F - BCR EPOXY 21 COMP B**

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

Target organs

Information not available

Route of exposure

Information not available

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

Target organs

Information not available

Route of exposure

Information not available

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

**11.2. Information on other hazards**

Based on the available data, the product contains the following endocrine disruptors in concentrations of 0.1% or greater by weight that may have endocrine disrupting effects on humans and cause adverse effects on the exposed individual or his or her progeny:

4,4'-ISOPROPYLIDENEDIPHENOL

**M400002F - BCR EPOXY 21 COMP B****SECTION 12. Ecological information**

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

**12.1. Toxicity**

## M-PHENYLENEBIS (METHYLAMINE)

LC50 - for Fish	87,6 mg/l/96h <i>Oryzias latipes</i>
EC50 - for Crustacea	15,2 mg/l/48h <i>Daphnia magna</i>
EC50 - for Algae / Aquatic Plants	20,3 mg/l/72h <i>Pseudokirchnerella subcapitata</i>

## 4,4'-ISOPROPYLIDENEDIPHENOL

LC50 - for Fish	9,4 mg/l/96h <i>Menidia menidia</i>
EC50 - for Crustacea	10,2 mg/l/48h <i>Daphnia magna</i>

**12.2. Persistence and degradability**

## M-PHENYLENEBIS (METHYLAMINE)

Solubility in water	1000 - 10000 mg/l
Rapidly degradable	

## BENZYL ALCOHOL

Rapidly degradable

2,4,6-TRIS(DIMETHYLAMINOMETHYL)  
PHENOL

Solubility in water	> 10000 mg/l
NOT rapidly degradable	

## 4,4'-ISOPROPYLIDENEDIPHENOL

Solubility in water	301 mg/l
Rapidly degradable	

**12.3. Bioaccumulative potential**

## M-PHENYLENEBIS (METHYLAMINE)

Partition coefficient: n-octanol/water	0,18
--	------

## BENZYL ALCOHOL

Partition coefficient: n-octanol/water	1,1
--	-----

2,4,6-TRIS(DIMETHYLAMINOMETHYL)  
PHENOL

Partition coefficient: n-octanol/water	-0,66
--	-------

**M400002F - BCR EPOXY 21 COMP B**

4,4'-ISOPROPYLIDENEDIPHENOL

Partition coefficient: n-octanol/water 3,4

**12.4. Mobility in soil**

4,4'-ISOPROPYLIDENEDIPHENOL

Partition coefficient: soil/water 2,95

**12.5. Results of PBT and vPvB assessment**

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

**12.6. Endocrine disrupting properties**

Based on the available data, the product contains the following endocrine disruptors in concentrations of 0.1% or greater by weight that may have endocrine disrupting effects on the environment and on animal species causing adverse effects on the exposed organisms or on their progeny:

4,4'-ISOPROPYLIDENEDIPHENOL

**12.7. Other adverse effects**

Information not available

**SECTION 13. Disposal considerations**

Non-hardened material (such as expired or damaged products and/or rejects): e.g.

08 04 09\* Glue and sealing materials waste containing organic solvents or other dangerous substances

Hardened material, e.g.:

08 04 10 Glue and sealing materials waste or other dangerous substances, other than classified under 08 04 09.

Contaminated packaging

Untaminated packaging may be taken for recycling.

Packaging that cannot be cleaned should be disposed of as for product.

15 01 10\* Packaging containing residues of or contaminated by dangerous substances

**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

**SECTION 14. Transport information****14.1. UN number or ID number**

ADR / RID, IMDG, 3259

IATA:



**M400002F - BCR EPOXY 21 COMP B**

**14.2. UN proper shipping name**

ADR / RID: AMINES, SOLID, CORROSIVE, N.O.S. (M-FENILENEBIS (METILAMMINA), 2,4,6-TRI(DIMETIL-AMINOMETILE)  
FENOLO, ALCOL BENZILICO)  
IMDG: AMINES, SOLID, CORROSIVE, N.O.S. (M-FENILENEBIS (METILAMMINA), 2,4,6-TRI(DIMETIL-AMINOMETILE)  
FENOLO, ALCOL BENZILICO)  
IATA: AMINES, SOLID, CORROSIVE, N.O.S. (M-FENILENEBIS (METILAMMINA), 2,4,6-TRI(DIMETIL-AMINOMETILE)  
FENOLO, ALCOL BENZILICO)

**14.3. Transport hazard class(es)**

ADR / RID: Class: 8 Label: 8  
IMDG: Class: 8 Label: 8  
IATA: Class: 8 Label: 8



**14.4. Packing group**

ADR / RID, IMDG, IATA: II

**14.5. Environmental hazards**

ADR / RID: NO  
IMDG: NO  
IATA: NO

**14.6. Special precautions for user**

In the standard packaging the product is transportable in LQ. For IATA (Cargo and Pass) packaging instruction Y845.

ADR / RID:	HIN - Kemler: 80	Limited Quantities: 1 kg	Tunnel restriction code: (E)
	Special provision: -		
IMDG:	EMS: F-A, S-B	Limited Quantities: 1 kg	
IATA:	Cargo:	Maximum quantity: 15 Kg	Packaging instructions: 863
	Pass.:	Maximum quantity: 15 Kg	Packaging instructions: 859
	Special provision:	A3, A803	

**14.7. Maritime transport in bulk according to IMO instruments**



**M400002F - BCR EPOXY 21 COMP B**

Information not relevant

## SECTION 15. Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

None

Product

Contained substance

None

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

Not applicable

Substances in Candidate List (Art. 59 REACH)

4,4'-ISOPROPYLIDENEDIPHENOL

REACH Reg.: 01-2119457856-23

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

### 15.2. Chemical safety assessment

**M400002F - BCR EPOXY 21 COMP B**

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

**SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Desen. Expl. 3</b>	Desensitised explosives, category 3
<b>Repr. 1B</b>	Reproductive toxicity, category 1B
<b>Acute Tox. 4</b>	Acute toxicity, category 4
<b>Skin Corr. 1</b>	Skin corrosion, category 1
<b>Eye Dam. 1</b>	Serious eye damage, category 1
<b>STOT SE 3</b>	Specific target organ toxicity - single exposure, category 3
<b>Skin Sens. 1</b>	Skin sensitization, category 1
<b>Aquatic Chronic 2</b>	Hazardous to the aquatic environment, chronic toxicity, category 2
<b>Aquatic Chronic 3</b>	Hazardous to the aquatic environment, chronic toxicity, category 3
<b>H207</b>	Fire or projection hazard; increased risk of explosion if desensitising agent is reduced.
<b>H360F</b>	May damage fertility.
<b>H302</b>	Harmful if swallowed.
<b>H312</b>	Harmful in contact with skin.
<b>H332</b>	Harmful if inhaled.
<b>H314</b>	Causes severe skin burns and eye damage.
<b>H318</b>	Causes serious eye damage.
<b>H335</b>	May cause respiratory irritation.
<b>H317</b>	May cause an allergic skin reaction.
<b>H411</b>	Toxic to aquatic life with long lasting effects.
<b>H412</b>	Harmful to aquatic life with long lasting effects.
<b>EUH071</b>	Corrosive to the respiratory tract.

**LEGEND:**

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train



**M400002F - BCR EPOXY 21 COMP B**

- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

**GENERAL BIBLIOGRAPHY**

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
  2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
  3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
  4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
  5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
  6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
  7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
  8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
  9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
  10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
  11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
  12. Regulation (EU) 2016/1179 (IX Atp. CLP)
  13. Regulation (EU) 2017/776 (X Atp. CLP)
  14. Regulation (EU) 2018/669 (XI Atp. CLP)
  15. Regulation (EU) 2019/521 (XII Atp. CLP)
  16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
  17. Regulation (EU) 2019/1148
  18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
  19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
  20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
  21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- The Merck Index. - 10th Edition
  - Handling Chemical Safety
  - INRS - Fiche Toxicologique (toxicological sheet)
  - Patty - Industrial Hygiene and Toxicology
  - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
  - IFA GESTIS website
  - ECHA website
  - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

**Note for users:**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

**CALCULATION METHODS FOR CLASSIFICATION**

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

**Changes to previous review:**

The following sections were modified:

02 / 03 / 11 / 16.